

Media Conversion

Ideal Solution for Multiple FTTx Deployment

Commercial Media Converter

Standard Media Converter

- 10/100/1000Base-T to 100/1000Base-X
- Auto-Negotiation, Auto-MDI/MDIX
- 100M/10G Converter Optional
- SC/FC/ST/SFP Optional
- Operation Temp. 0~50°C
- External Power DC5~12V, 1A
- Dimension: 93*71*27mm



LFP Media Converter

- 10/100/1000Base-T to 1000Base-X
- Auto-Negotiation, Auto-MDI/MDIX
- 100M/10G Converter Optional
- SC/FC/ST/SFP Optional
- Operation Temp. -20~70°C
- External Power DC5~12V, 1A
- Dimension: 93*71*27mm



Ultra-compact Media Converter

- 10/100/1000Base-T to 1000Base-X
- Auto-Negotiation, Auto-MDI/MDIX
- SC/FC/ST/SFP Optional
- Operation Temp. -20~70°C
- External Power DC5V, 1A
- Dimension: 79*23*18mm



SFP to SFP Converter

- Single Mode to Multi-mode and Vice-versa
- Auto-Negotiation, Auto-MDI/MDIX
- 100M/1000M/10G Converter Optional
- SC/FC/ST/SFP Optional
- Operation Temp. 0~50°C
- External Power DC5V, 1A
- Dimension: 94*70.5*26.5mm



Industrial Media Converter

Industrial Media Converter

- 10/100/1000Base-T to 100/1000Base-X
- Auto-Negotiation, Auto-MDI/MDIX
- Operation Temp. Hardened -40~75°C
- Dual Power DC12~48V Input
- Dimension: 95*70*30mm



Industrial PoE Media Converter

- 10/100/1000Base-T to 1000Base-X
- PoE Watchdog/VLAN/Port Isolation/VIP & QoS
- Operation Temp. Hardened -40~75°C
- Dual Power DC48~58V Input
- Dimension: 143*104*48mm



Application

