

CSL3LR-24S02G-2A-S

Access Switch Layer 3 Lite Managed 24x1000M SFP, 2x10/100/1000M RJ45



Overview

This 24-port Gigabit SFP industrial switch delivers high-speed, stable, and flexible network performance for enterprise, data center, and industrial applications. It features 24 Gigabit SFP ports and 2 additional RJ45 uplink ports for versatile fiber and copper connectivity. With a 56 Gbps switching capacity and 41.67 Mpps forwarding rate, it ensures fast and reliable data transmission across large-scale networks.

Designed for continuous operation, the switch supports redundant power input, intelligent system monitoring, and wide environmental adaptability. Its durable metal housing, 6 kV surge protection, and rack-mount design make it ideal for mission-critical environments such as backbone aggregation, industrial networking, and security monitoring systems.

Features

- 24x1000M SFP ports and 2x10/100/1000M RJ45
- Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab standards
- Ethernet port 10/100/1000M adaptive
- Support port auto flip (Auto MDI/MDIX)
- Support WEB, TELNET, CLI, SSH, SNMP, RMON management

- CE/FCC/RoHS Certified

Specifications

Fixed Port	24x1000M SFP, 2x10/100/1000M RJ45 (Data)
Console Port	1*console port
Reset Key	1
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Packet Buffer	4.1Mbit SRAM
Jumbo Frame	10K Bytes
VLAN Address	4K
Transmission Distance	10BASE-T: Cat3, 4, 5 UTP (\leq 250m) 100BASE-TX: Cat5 or later UTP (150m) 1000BASE-TX: Cat6 or later UTP (150m) SFP: 1000M SMF/MMF optical module with max. distance \leq 120km
LED Indicators	PWR: Power LED SYS: System LED 1-2: 10/100/1000M Network connection indicator 3-26: SFP connection indicator MS: Master power LED SL: Slave power LED
Power	Internal Redundant AC100~240V, 0.5A, Max. 35W
Operating Temperature	-10~+55°C
Operating Humidity	5%~90% RH Non-condensing
Storage Temperature	-40~+75°C
Storage Humidity	5%~95% RH Non-condensing
Product Size (L x W x H)	440x227x45mm
Package Size (L x W x H)	515x300x95mm

N.W.	3.1kg
G.W.	4.1kg
Lightning Protection Level	6KV 8/20us; IP30
Installation	Rack-mount
Certificates	CE/FCC/RoHS
Warranty	1 year
Software Functions	
Port Shutdown	Support
Port Speed	Support auto negotiate, full-1000, full-100, half-100, full-10, half-10
Flow Control	Support full-duplex IEEE 802.3x, half-duplex back pressure
Storm Control	Support rate limit for broadcast, multicast, and DLF packets
Storm Constrain	Support the detection of broadcast packets, multicast packets, or multicast packets on the port, shutdown the port if the rate is over the threshold.
Port Mirror	Support
Port Rate Limit	Support port ingress and egress rate limit
Link Aggregation	Support manual link aggregation Support LACP dynamic link aggregation Supports up to 8 aggregation groups, each group up to 8 ports Support source MAC, destination MAC, source destination MAC, source IP, destination IP, source destination IP routing strategy
Port Isolation	Support
Jumbo Frame	Support up to 10KB
Cable Distance Diagnosis	Support
Redundant Port	Support
DDM of Fiber Ports	Support
MAC	
MAC Table Capacity	8K
MAC Table Management	Support
Forwarding Mode	Support IVL forwarding mode
Static MAC Address	Support
MAC Address Binding	Support
MAC Learning Control	Control the MAC learning based on port
VLAN	

Number of Vans	4K
802.1Q-based VLAN	Support
MAC-based VLAN	Support
IP-based VLAN	Support
Protocol-based VLAN	Support
PVLAN	Support
Voice VLAN	Support
VLAN Mapping	Support 1:1 mapping
QinQ	Support basic QinQ Support flexible QinQ
Reliability	
Spanning Tree Protocol	Support STP/RSTP/MSTP
Port Loop Detection	Support
EAPS	Support RFC3619
ERPS	Support G.8032/Y.1344
LLDP	Support LLDP & LLDP-MED
UDLD	Fully compatible with Cisco's UDLD protocol
IP	
ARP	Support static and dynamic ARP
IP Route	Support 0.0.0.0/0 route and other static route, but can't support L3 forwarding
VLAN Interface	Support 32 VLAN interfaces
Multicast	
Static Multicast MAC Address	Support
IGMP Snooping	Support
MLD Snooping	Support
MVR	Support
GMRP	Support
ACL	
Standard IP-based ACL	Support
Extended IP based ACL	Support
MAC IP-based ACL	Support
MAC ARP-based ACL	Support

IPv6-based ACL	Support
ACL Port Filtering	Support
Time-based ACL	Support
QoS	
Port Queue Number	8
Port Queue Scheduling Mode	Support WRR, SP, WFQ
Port-based Classification	Support
802.1p-based Classification	Support
DSCP-based Classification	Support
ACL-based Classification	Support
	Support packets mapping to queue
	Support COS or DSCP Remarking
QoS Policy	Support rate limits of data flow
	Support data flow statistics
	Support mirroring of data flow
DHCP	
DHCPv4 Client	Support
DHCPv6 Client	Support
DHCP Snooping	Support
DHCP Relay	Support
DHCP Server	Support
DHCP Option 82	Support
Management	
	Support Console, TELNET and SSH
	Support multiple TELNET connections based on IPv4 and IPv6
CLI Management	Support multiple SSH connections based on IPv4 and IPv6
	Support running configuration rollback
	Support ZTP (Zero Touch Configuration)
WEB Management	Support
	Support SNMP v1, v2c, v3
SNMP Management	Support SNMP TRAP
	Support lots of standard and private MIBs
	Support SNMP based on IPv4 and IPv6
User Management	Support multiple user management

TACACS+	Support switch authentication via TACACS+ server remote username and password Support password encryption in PAP and CHAP mode Support TACACS+ server to authorize the switch's commands Support TACACS+ based on IPv4 and IPv6
Log Management	Support local log management Support SYSLOG based on IPv4 and IPv6
Log Management	Support local log management Support SYSLOG based on IPv4 and IPv6
RMON	Support RMON 1, 2, 3 and 9 groups
Cluster Management	Support NDP Support NTDP Support manual and automatic joining of cluster groups Support cluster unified management
OAM	Support 802.3ah Support 802.1ag
Configuration File	Support TFTP transmission based IPv4 and IPv6 Support SFTP transmission based IPv4 and IPv6 Support SFTP Client and SFTP Server
Upgrade Software	Support TFTP transmission based IPv4 and IPv6 Support SFTP transmission based IPv4 and IPv6 Support SFTP Client and SFTP Server
Clock Management	Support local clock management Support SNTP based IPv4 and IPv6
Security	
Switch Management Security	Support enabling and disabling TELNET, SSH, WEB and SNMP services Support TELNET, SSH, WEB and SNMP services to bind to standard IP ACLU Support for limiting the number of TELNET connections
CPU Protection	The switch's own security protection prevents large data streams from attacking the switch itself.
AAA	Support 802.1x Support RADIUS Supports authentication, authorization, and accounting through RADIUS server Support port-based and MAC-based 802.1x Support 802.1x guest VLAN
IP MAC Binding	Support static configuration of IP, MAC and port binding

DHCP SNOOPING	Support dynamic ARP binding to prevent ARP spoofing Support dynamic IP, MAC and port binding Support fixed port to connect to DHCP server to prevent private connection to DHCP server
Prevent ARP Spoofing	Support manually configuring MAC CARP-based ACL rules to prevent ARP spoofing. Support the DHCP SNOOPING function. During the process of obtaining an IP address by DHCP, the switch dynamically binds ARP to the port to prevent ARP spoofing.
IPv6	
IPv4/IPv6 Dual Protocol Stack	Support
IPv6 Address	Support manual address configuration, stateless address auto-configuration and stateful address configuration obtained through DHCPv6 client
IPv6 Neighbor Discovery	Support
ICMPv6	Support
IPv6 Path MTU Discovery	Support
Debugging	
PING	Support
PING6	Support
TRACEROUTE	Support
TELNET Client	Support TELNET client based IPv4 and IPv6
SSH Client	Support SSH client based IPv4 and IPv6
TWAMP	Support TWAMP server and session-reflector

Order Information

P/N	Description
CSL3LR-24S02G-2A-S	Access Switch Layer 3 Lite Managed 24x1000M SFP, 2x10/100/1000M RJ45 Internal Redundant AC100~240V



<https://www.lanaotek.com>



Specifications & design are subject to change without prior notice.

For more details, please email to info@lanaotek.com. Copyright©2025 lanaotek.com All Rights Reserved